






ALL TIE-INS TO BE BLOCKED  
AND RESTRAINED  
FOR BLOCKING AND  
RESTRAINING TABLE  
SEE SHEET 8  
PROJECT PRESSURE  
100 PSI



0	1/29/24	PROPOSED TO CONSTRUCTION	AH
NO	DATE	REVISION	INTL
AQUA PENNSYLVANIA, INCORPORATED			
762 LANCASTER AVENUE, BRYN MAWR, PA, 19010			
PROJECT PLAN FOR: <b>DASH AVENUE PROJECT</b>			
DASH AVENUE, TURNER LANE (PRIVATE), VALLEY VIEW ROAD UPPER PROVIDENCE TOWNSHIP, DELAWARE COUNTY			
DRAWN BY:	RCC	CHK'D BY:	BCAD
DATE:	09/14/23	SCALE:	1" = 30'
PROJECT No:	1458.14	ACTIVITY No:	100088561
APPROVED			A - 67437
			SHEET 1 OF 8





## LEGEND

§ [REDACTED] § = PROPOSED WATER MAIN

 = ABANDONED WATER MAIN

0	1/29/24	PROPOSED TO CONSTRUCTION	AH
NO	DATE	REVISION	INTL
<p style="text-align: center;"><b>AQUA PENNSYLVANIA, INCORPORATED</b>  762 LANCASTER AVENUE, BRYN MAWR, PA., 19010</p> <p style="text-align: center;"><b>PROJECT PLAN FOR:</b>  <b>DASH AVENUE PROJECT</b>  <b>COLLINS AVENUE, DASH AVENUE</b>  <b>UPPER PROVIDENCE TOWNSHIP, DELAWARE COUNTY</b></p>			
DRAWN BY: RCG		CHK'D BY: BCAD	EXT No: 20007-S
DATE: 09/14/23		SCALE: 1" = 30'	PLATE: F-31
PROJECT No: 1458.14		ACTIVITY No: 100088561	<b>A - 67437</b>
APPROVED		SHEET 3 OF 8	

**ALL TIE-INS TO BE BLOCKED  
AND RESTRAINED**

**FOR BLOCKING AND  
RESTRAINING TABLE  
SEE SHEET 8**

**PROJECT PRESSURE  
100 PSI**

# MATCHLINE B SEE SHEET 2

SCALE

LEGEND

 = PROPOSED WATER MAIN

 = ABANDONED WATER MAIN

 = EXISTING WATER MAIN

**MATCHLINE B**  
SEE SHEET 3

**GILBERT STREET**

HOUSE 521  
HOUSE 515  
HOUSE 511  
HOUSE 101  
HOUSE 100  
HOUSE 14  
HOUSE 10  
GARAGE 460

15' C/W  
16' C/W  
16' C/W  
40' R/W  
17' C/W  
7'  
17' C/W  
5'  
17' C/W  
5'  
17' C/W  
375'  
33' R/W  
15' C/W  
17' C/W  
5'  
40' R/W  
17' C/W  
5'  
17' C/W  
5'  
17' C/W  
33' R/W  
15' C/W  
17' C/W  
4' (REF)  
2" P/GAS  
33' R/W  
17' C/W  
17' C/W  
33' R/W  
15' C/W  
17' C/W  
2" P/GAS  
33' R/W

**COLLINS AVENUE**

280' TO 8"x6" SWIVEL TEE  
108' TO MATCHLINE

8"x4" TEE (MJ)  
4" RSGV (MJ)  
RESTRAIN 15' BRANCH SIDE  
8" RSGV (MJ)  
RESTRAIN 19' BOTH DIRECTIONS

**OLD STATE ROAD**

6" x6" TAP SLEEVE (MJ)  
6" RSGV (MJ)  
RESTRAINED JOINT  
8"x6" REDUCER (MJ)  
RESTRAIN 8' ON 8" DIA SIDE  
HOUSE 460  
OLD STATE ROAD

**SCALE**

0 30 60 FEET

The diagram illustrates three house lots arranged in a triangular pattern. The top lot is a trapezoid containing the text "HOUSE 507". The bottom-left lot is a trapezoid containing the text "HOUSE 503". The bottom-right lot is a trapezoid containing the text "HOUSE 475".

0	1/29/24	PROPOSED TO CONSTRUCTION	AH
NO	DATE	REVISION	INTL
<p style="text-align: center;"><b>AQUA PENNSYLVANIA, INCORPORATED</b>  762 LANCASTER AVENUE, BRYN MAWR, PA., 19010</p>			
<p style="text-align: center;"><b>PROJECT PLAN FOR:</b></p> <p style="text-align: center;"><b>DASH AVENUE PROJECT</b></p> <p style="text-align: center;"><b>COLLINS AVENUE, GILBERT STREET, OLD STATE ROAD</b></p> <p style="text-align: center;"><b>UPPER PROVIDENCE TOWNSHIP, DELAWARE COUNTY</b></p>			
DRAWN BY: RCG		CHK'D BY: BCAD	EXT No: 20007-S
DATE: 09/14/23		SCALE: 1" = 30'	PLATE: F-31
PROJECT No: 1458.14		ACTIVITY No: 100088561	<b>A - 67437</b>
APPROVED			
		SHEET 4 OF 8	

**PATA 103**

1. The RIGHT REVERSE CURVE sign shall only be used when lane shifts onto shoulder.
2. When a shadow vehicle is not used, distance E is measured from the end of the taper to the beginning of the work space.



Sign Spacing, Channelizing Device Spacing, Buffer Space, and Roll Ahead Space

Speed (MPH)	Channelizing Devices Spacing	Sign Spacing		Buffer Space	Roll Ahead Space
		Urban (Feet)	Rural (Feet)		
25	50	100 - 200	500 - 800	155	150
30	60	100 - 200	500 - 800	200	150
35	70	100 - 200	500 - 800	250	150
40	80	350 - 500	500 - 800	305	150
45	90	350 - 500	500 - 800	360	150
50	100	350 - 500	500 - 800	425	250
55	110	350 - 500	500 - 800	495	250

Taper Lengths and Minimum Number Of Channelizing Devices

Speed (MPH)	Shifting Taper: 1/2L		Shoulder Taper: 1/3L		50' Per Lane Taper	
	Length (Feet)	Minimum Number Of Devices	Length (Feet)	Minimum Number Of Devices	Length (Feet)	Minimum Number Of Devices
25	65	6	45	6	50	6
30	90	6	60	6	50	6
35	125	6	85	6	50	6
40	160	6	110	6	50	6
45	270	7	180	6	50	6
50	300	7	200	6	50	6
55	330	7	220	6	50	6

**PATA 107**

1. Flaggers shall be clearly visible to traffic for a minimum distance of E.
2. For operations of 15 minutes or less:
  - a) The ROAD WORK, ONE LANE ROAD, and FLAGGER SYMBOL signs are not required.
  - b) All channelizing devices may be eliminated if a shadow vehicle is present and the operation does not proceed against normal traffic flow.
3. When a shadow vehicle is not used, distance E is measured from the end of the taper to the beginning of the work space.



Sign Spacing, Channelizing Device Spacing, Buffer Space, and Roll Ahead Space

Speed (MPH)	Channelizing Devices Spacing	Sign Spacing		Buffer Space	Roll Ahead Space
		Urban (Feet)	Rural (Feet)		
25	50	100 - 200	500 - 800	155	150
30	60	100 - 200	500 - 800	200	150
35	70	100 - 200	500 - 800	250	150
40	80	350 - 500	500 - 800	305	150
45	90	350 - 500	500 - 800	360	150
50	100	350 - 500	500 - 800	425	250
55	110	350 - 500	500 - 800	495	250

Taper Lengths and Minimum Number Of Channelizing Devices

Speed (MPH)	50' Per Lane Taper	
	Length (Feet)	Minimum Number Of Devices
25	50	6
30	50	6
35	50	6
40	50	6
45	50	6
50	50	6
55	50	6

**PATA 109 (A Through L)**

1. PATA 109 drawings show work spaces on roads that approach and depart T-intersections with through-roads. Single-flagger or multi-flagger intersection control is illustrated for intersections with three types of permanent control:

- a) One-Way Stop
- b) All-Way Stop
- c) Traffic Signal

2. Flaggers shall be clearly visible to traffic for a minimum distance of E.

3. For operations of 15 minutes or less:

- a) The ROAD WORK, ONE LANE ROAD, and FLAGGER SYMBOL signs are not required.
- b) All channelizing devices may be eliminated if a shadow vehicle is present and the operation does not proceed against normal traffic flow.

4. When a shadow vehicle is not used, distance E is measured from the end of the taper to the beginning of the work space.






Sign Spacing, Channelizing Device Spacing, Buffer Space, and Roll Ahead Space

Speed (MPH)	Channelizing Devices Spacing	Sign Spacing		Buffer Space	Roll Ahead Space
		Urban (Feet)	Rural (Feet)		
25	50	100 - 200	500 - 800	155	150
30	60	100 - 200	500 - 800	200	150
35	70	100 - 200	500 - 800	250	150
40	80	350 - 500	500 - 800	305	150
45	90	350 - 500	500 - 800	360	150
50	100	350 - 500	500 - 800	425	250
55	110	350 - 500	500 - 800	495	250

Taper Lengths and Minimum Number Of Channelizing Devices

Speed (MPH)	50' Per Lane Taper	
	Length (Feet)	Minimum Number Of Devices
25	50	6
30	50	6
35	50	6
40	50	6
45	50	6
50	50	6
55	50	6

**PATA 103****PATA 107****PATA 109 (A Through L)**

NOTE:  
CONTRACTOR TO SELECT APPROPRIATE TRAFFIC CONTROL OPTION (PATA 109-A THROUGH PATA 109-L)  
BASED ON TYPE OF PERMANENT CONTROL AND FIELD CONDITIONS.




**PENNDOT CONSTRUCTION NOTES:**

1. TOWNSHIP TO BE NOTIFIED PRIOR TO WORKING NEAR SCHOOL SIGNALS AND SHALL MARK OUT AS REQUIRED.
2. SHOULDER AREAS PRONE TO WASHOUT SHALL BE PAVED.
3. ANY DAMAGE TO TREES OR CUT SLOPES CAUSING THEM TO FAIL SHALL BE THE RESPONSIBILITY OF THE PERMITTEE.
4. MAIN TO BE SLEEVED OR ENCASED WHERE PASSING THROUGH GUARDRAIL.
5. PERMITTEE AND HIS CONTRACTOR ARE RESPONSIBLE FOR FAMILIARIZING THEMSELVES WITH THE REQUIRED EROSION AND SEDIMENTATION CONTROL MEASURES. APPROPRIATE CONTROLS ARE TO BE IN PLACE PRIOR TO SITE DISTURBANCE, CONTINUALLY MAINTAINED DURING CONSTRUCTION UNTIL REMOVED AND LEFT IN PLACE UNTIL SITE IS STABILIZED.
6. TOWNSHIP TO BE NOTIFIED PRIOR TO WORKING NEAR TRAFFIC SIGNAL LOOPS AND SHALL MARK OUT AS REQUIRED.
7. A BRIDGE OCCUPANCY LICENSE SHALL BE OBTAINED FOR THE STRUCTURE EXCEPT IN EMERGENCY SITUATION.
8. EACH FLAGGER STATION SHALL BE ILLUMINATED AT NIGHT WITH AN OVERHEAD LIGHTING SOURCE HAVING 30,000 TO 40,000 LUMENS MINIMUM OF LIGHT OUTPUT FOR AN AREA OF NOT LESS THAN 7,500 SQUARE FEET. THE LIGHTING SOURCE SHALL HAVE A MINIMUM COLOR TEMPERATURE OF 3,000 DEGREES AND A MAXIMUM OF 4,000 DEGREES. POSITION THE LIGHT SO THE FLAGGERS CAN BE SEEN AND NOT CAUSE EXCESSIVE GLARE TO MOTORIST TRAVELING THROUGH THE WORK ZONE.
9. NOTIFY THE DISTRICT 6-0 REGIONAL TRAFFIC MANAGEMENT CENTER (RTMC) 610-205-6934 FIFTEEN (15) MINUTES IN ADVANCE OF ANY PROPOSED LANE OR SHOULDER RESTRICTION, ROAD CLOSURE, OR ANY OPERATION IMPEDING THE FLOW OF TRAFFIC. NOTIFY THE RTMC WHEN THE ROAD IS RESTORED TO NORMAL OPERATION.
10. SUBMIT A COMPLETED M-937R FORM TO THE DISTRICT HAULING PERMIT OFFICE (610-205-6787) AND THE INSPECTOR-IN-CHARGE TEN WORKING DAYS IN ADVANCE OF ALL TRAFFIC RESTRICTIONS.
11. PROTECT DROP-OFFS ADJACENT TO A TRAVEL LANE IN ACCORDANCE WITH PUBLICATION 408, SECTION 901.3(j).
12. THE WORK MUST BE PERFORMED IN WAY THAT WILL NOT CREATE A HAZARD FOR VEHICLE TRAFFIC OR PEDESTRIAN TRAFFIC.
13. COORDINATE DELIVERY OF EQUIPMENT, MATERIAL TO MINIMIZE INCONVENIENCE TO TRAVELING PUBLIC.
14. REPLACE ALL PAVEMENT MARKINGS WHICH HAD BEEN REMOVED DURING CONSTRUCTION, UNLESS OTHERWISE NOTED.


**NOTES:**

1. ALL SIGNS SHALL BE REFLECTORIZED.
2. ALL FLAGGERS MUST BE IN COMMUNICATION WITH EACH OTHER AND PENNDOT CERTIFIED.
3. EACH FLAGGER SHOULD BE CLEARLY VISIBLE TO THE TRAFFIC WHICH IS BEING CONTROLLED.
4. NOTIFY THE LOCAL MUNICIPALITY WHEN A SIGNALIZED INTERSECTION FALLS WITHIN THE WORK ZONE. DO NOT FLAG A SIGNALIZED INTERSECTION WITHOUT THE MUNICIPALITY PLACING THE SIGNAL ON FLASH.
5. NO OPEN TRENCHES WILL BE PERMITTED AT NIGHT.
6. MAINTAIN ALL ACCESS TO DRIVEWAYS AND SIDE ROADS.
7. NO LANE CLOSURES OR TRAFFIC RESTRICTIONS ON LEGAL HOLIDAYS, AND BETWEEN THE HOURS OF 6:00 AM 9:00 AM AND 3:00 PM TO 7:00 PM.

8. NOTIFY LOCAL EMERGENCY UNITS (POLICE, FIRE, MEDICAL, ETC.), LOCAL BUSINESSES, SCHOOL DISTRICT, THE LOCAL MEDIA AND THE REPRESENTATIVE TEN (10) WORKING DAYS IN ADVANCE OF THE START OF WORK.
9. THE CONTRACTOR IS REQUIRED TO SUBMIT A ROAD RESTRICTION FORM TO THE DISTRICT 6-0 PRESS OFFICE ONE WEEK IN ADVANCE OF ANY LANE CLOSURES AND TWO




0	1/29/24	PROPOSED TO CONSTRUCTION	AH
NO	DATE	REVISION	INTL
AQUA PENNSYLVANIA, INCORPORATED 762 LANCASTER AVENUE, BRYN MAWR, PA, 19010			
PROJECT PLAN FOR: <b>DASH AVENUE PROJECT</b> ROAD RESTORATION DETAILS UPPER PROVIDENCE TOWNSHIP, DELAWARE COUNTY			
DRAWN BY:	RCC	CHK'D BY:	BCAD
DATE:	09/14/23	SCALE:	N.T.S.
PROJECT No:	1458.14	ACTIVITY No:	100088561
APPROVED	<b>A - 67437</b>		
	SHEET 6 OF 8		



**MINIMUM CONCRETE VOLUMES AND STEEL STRAP SIZES REQUIRED FOR BLOCKING 6", 8", 12" AND 16" VERTICAL BENDS**

**DETAILS (NTS)**



KEY	PIPE DIAMETER (INCH)	PRESSURE (PSI)	BEND ANGLE (DEGREE)	CONCRETE REQUIRED (CU YD)	STEEL STRAP SIZE	"R" STRAP RADIUS	ANCHOR BOLT DIAMETER "D" AND NUMBER REQUIRED PER STRAP	EMBEDMENT LENGTH
<b>A</b>	<b>6</b>	0-100	ALL	1.0	1/4" x 2 1/2"	3 5/8"	(2) 3/4"	24"
<b>A-1</b>	<b>6</b>	101-200	ALL	2.5	1/4" x 2 1/2"	3 5/8"	* (2) 1"	36"
<b>B</b>	<b>8</b>	0-100	ALL	2.0	3/8" x 3"	4 3/4"	* (2) 1"	36"
<b>B-1</b>	<b>8</b>	101-200	45	3.0	3/8" x 3"	4 3/4"	* (2) 1"	36"
<b>B-2</b>	<b>8</b>	101-200	90	4.0	3/8" x 3"	4 3/4"	(4) 1"	36"
<b>C</b>	<b>12</b>	0-100	ALL	4.5	1/2" x 3"	6 3/4"	(4) 1"	36"
<b>C-1</b>	<b>12</b>	101-200	45	6.0	(2) 1/2" x 3"	6 3/4"	(4) 1"	36"
<b>C-2</b>	<b>12</b>	101-200	90	8.5	(2) 1/2" x 3"	6 3/4"	(4) 1"	36"
<b>D</b>	<b>16</b>	0-100	ALL	10.0	5/8" x 4"	8 3/4"	(4) 1 1/4"	48"
<b>D-1</b>	<b>16</b>	101-200	45	11.0	(2) 5/8" x 4"	8 3/4"	(4) 1 1/4"	48"
<b>D-2</b>	<b>16</b>	101-200	90	15.0	(2) 5/8" x 4"	8 3/4"	(4) 1 1/4"	48"

NOTES:  
1. ALL STEEL SHALL CONFORM TO ASTM A-36  
2. (2) STRAPS ARE REQUIRED, EACH WITH (4)-1" DIAMETER ANCHOR BOLTS FOR CASES C-1 AND C-2  
3. REFER TO AQUA DRAWING E-4453 FOR USE AS PIPE AND VALVE CLAMP  
4. CONTACT ENGINEERING DEPARTMENT FOR DESIGN ON PRESSURE EXCEEDING 200 PSI OR IF PIPE SIZE IS LARGER THAN 12"  
5. COAT ALL EXPOSED METAL WITH 12 MILS OF ROSKOTE.  
6. BOLT LENGTH WILL EQUAL "EMBEDMENT LENGTH" + SHIM + 1/2" OD OF PIPE + 3-1/2".

**VERTICAL BLOCKING TABLE**

MINIMUM RESTRAINT LENGTH FOR VERTICAL FITTINGS		
PROFILE VIEW (NTS)		
<b>3.5' MIN COVER / COMPACTED 1.5:1 SAFETY FACTOR / EBBA</b>		
<b>DIA. (INCH)</b> <b>MATERIAL</b>		
<b>Backfill</b>		
2A Modify (GW)	6"	DIP
Sand (SW)	6"	Poly Wrapped DIP
Sand (SW)	6"	PVC
2A Modify (GW)	8"	DIP
Sand (SW)	8"	Poly Wrapped DIP
Sand (SW)	8"	PVC
2A Modify (GW)	12"	DIP
Sand (SW)	12"	Poly Wrapped DIP
Sand (SW)	12"	PVC
2A Modify (GW)	16"	DIP
Sand (SW)	16"	Poly Wrapped DIP
Sand (SW)	16"	PVC

NOTES:  
1. IMAGES ARE DI FITTINGS WITH PVC PIPE FOR CLARITY OF THE FITTING.  
IMAGES INCLUDE MECHANICAL RESTRAINT SYSTEM. PREFERRED METHOD IS THE USE OF (SURE/STOP FIELD LOK) RESTRAINING GASKET AT PUSH ON JOINTS AND APPROPRIATE MEGALUG RESTRAINTS AT MECHANICAL JOINTS (MJ).  
2. RESTRAINED JOINT METHOD IS INTENDED TO BE USED ON NEW PIPE ONLY (NOT RETROFITTED TO EXISTING PIPE TO REMAIN). WHERE RESTRAINT AT CONNECTIONS TO EXISTING PIPE IS REQUIRED, USE VERTICAL STRAPPING METHOD.  
3. FOR PRESSURES OVER 200 PSI AND DEPTHS OF COVER LESS THAN 3.5 FT. PLEASE CONTACT ENGINEERING DEPARTMENT FOR REQUIRED RESTRAINED LENGTH IF NOT OTHERWISE SPECIFIED.

**VERTICAL RESTRAINED JOINT TABLE**


**MINIMUM THRUST BLOCK AREAS REQUIRED (SQUARE FEET (SF) OF CONTACT SURFACE AREA ALONG TRENCH WALL)**

**HORIZONTAL FITTINGS PLAN VIEW (NTS)**

$$bh_{tow} = \frac{s_f P A}{s_b}$$

$$bh_{bend} = \frac{s_f 2 P A \sin(\theta/2)}{s_b}$$

$$A = \frac{\pi}{4} D^2$$



**4' COVER 1.5:1 SAFETY FACTOR**

**DIA. (INCH) MATERIAL**

**DEAD-END / C&P / BO / HYD/TEE**

**HORIZ 90 BEND**

**HORIZ 45 BEND**

**HORIZ 22 1/2 BEND**

**HORIZ 11 1/4 BEND**

**PSI SF**

100	150	200	100	150	200	100	150	200	100	150	200	100	150	200
2	3	4	3	4	6	2	2	3	3	4	6	1	1	2
4	6	8	5	8	11	3	4	6	1	2	3	1	1	1
8	13	17	12	18	24	6	10	13	3	5	7	2	2	3
15	23	30	21	32	43	12	17	23	6	9	12	3	4	6
24	35	47	33	50	67	18	27	36	9	14	18	5	7	9
34	51	68	48	72	96	26	39	52	13	20	26	7	10	13
53	80	106	75	112	150	41	61	81	21	31	41	10	16	21


**NOTES:**

1. IMAGES ARE DI FITTINGS WITH PVC PIPE FOR CLARITY OF THE FITTING.
2. CONTACT ENGINEERING DEPARTMENT FOR PRESSURES ABOVE 200 PSI.

**HORIZONTAL BLOCKING TABLE**

**MINIMUM RESTRAINT LENGTH FOR HORIZONTAL FITTINGS**

**HORIZONTAL PLAN VIEW (NTS)**



**4' COVER / COMPACTED 1.5:1 SAFETY FACTOR / EBBA**

**100 150 200 PSI/LF PSI/LF PSI/LF**

**INLINE VALVE/BLOW OFF/TEE BRANCH**

**HORIZ 90 BEND**

**HORIZ 45 BEND**

**HORIZ 22 1/2 BEND**

**HORIZ 11 1/4 BEND**

**PSI/LF PSI/LF PSI/LF**

100	150	200	100	150	200	100	150	200	100	150	200	100	150	200
15'	22'	29'	7'	10'	13'	3'	4'	6'	2'	2'	3'	1'	2'	2'
42'	63'	84'	9'	13'	17'	4'	6'	8'	2'	3'	4'	1'	2'	2'
23'	34'	46'	8'	11'	15'	3'	5'	6'	2'	3'	3'	1'	2'	2'
19'	29'	38'	8'	12'	16'	4'	5'	7'	2'	3'	4'	1'	2'	2'
55'	82'	110'	12'	17'	23'	5'	7'	10'	3'	4'	5'	2'	3'	3'
30'	45'	60'	10'	15'	19'	4'	6'	8'	2'	3'	4'	1'	2'	2'
27'	40'	54'	12'	17'	23'	5'	7'	10'	3'	4'	5'	2'	3'	3'
78'	117'	156'	16'	24'	31'	7'	10'	13'	4'	5'	7'	2'	3'	4'
43'	64'	85'	14'	20'	27'	6'	9'	12'	3'	4'	6'	2'	3'	3'
35'	52'	69'	15'	22'	29'	6'	9'	12'	3'	5'	6'	2'	3'	3'
101'	151'	201'	20'	30'	40'	9'	13'	17'	4'	6'	8'	2'	3'	4'
55'	83'	110'	17'	26'	34'	8'	11'	15'	5'	7'	9'	3'	4'	5'
42'	63'	84'	18'	26'	35'	8'	11'	15'	4'	6'	7'	2'	3'	4